

820116, (HSSCo L/S Worm Pattern)



Material Group	v _c (m/min)	f _n (mm/rev)														
		ø1.0 -1.9	ø2.0 -2.9	ø3.0 -3.9	ø4.0 -4.9	ø5.0 -5.9	ø6.0 -6.9	ø7.0 -7.9	ø8.0 -9.9	ø10.0 -11.9	ø12.0 -13.5	ø14.0 -15.5	ø16.0 -17.5	ø18.0 -19.5	ø20.0	
P	11															
	12	15 (13-18)	-	0.03	0.05	0.06	0.06	0.08	0.09	0.10	0.12	0.13	-	-	-	-
	13															
	14															
H	15	10 (8-13)	-	0.02	0.04	0.05	0.05	0.06	0.08	0.10	0.12	0.13	-	-	-	-
	16															
K	31	22 (20-25)	-	0.06	0.10	0.13	0.13	0.16	0.18	0.20	0.23	0.25	-	-	-	-
	32															
	33	9 (7-12)	-	0.05	0.08	0.10	0.10	0.13	0.15	0.17	0.20	0.22	-	-	-	-
	34															

v_c - cutting speed (m/min)

n - RPM (rev/min)

f_n - feed rate (mm/rev)

ø - drill diameter (mm)

$$\text{To calculate RPM from cutting speed: } n = \frac{v_c \cdot 1000}{\pi \cdot \phi}$$

$$\text{To calculate cutting speed from RPM: } v_c = \frac{n \cdot \pi \cdot \phi}{1000}$$

All recommendations are based on ideal machining conditions. Adjustments may need to be made according to your set-up. The recommendations for speeds, feeds and other parameters presented in this chart are nominal recommendations and should be considered only as good starting points.